

**ISO 9001 CERTIFIED**

## Model 3446

**10 - 130 MHz, 1 kW pulsed,  
solid-state, RF power  
amplifier system**

### Electrical specifications:

Frequency range	10 - 130 MHz
Pulse power (min.) into 50 ohms	1,000 W
CW power (max) into 50 ohms	100 W
Linearity ( $\pm 1$ dB)	0 - 800 W
Gain (typ.)	65 dB
Gain flatness, Typical	$\pm 5$ dB
Input/Output impedance	50 ohms
Input VSWR	< 2:1
Pulse width	20 ms, 100 ms with long pulse option
Duty cycle	Up to 10%
Amplitude rise/fall time	250 ns typ.
Amplitude droop	5% to rated pulse width, typ.
Phase change/output power	10° to rated linear power, typ.
Phase error overpulse	4° to rated pulse width, typ.
Noise figure	11 dB typ.
Output noise (blanked)	< 10 dB over thermal
Blanking delay	< 1 $\mu$ s on/off, TTL signal
Protection	1. Infinite VSWR at rated power 2. Output overdrive 3. Over duty cycle/pulse width 4. Over temperature

### Supplemental characteristics:

Connectors, rear panel	1. RF input: BNC (F) 2. RF output: Type N (F) 3. Noise blanking: BNC (F) 4. Interface: 25 pin D(F), EMI filtered		
Indicators, front panel	1. AC power on	5. Over temperature	
	2. Peak power meter	6. Overdrive, Fwd/Ref	
	3. Over pulse width	7. CW mode	
	4. Over duty cycle/Standby		
System monitors	1. Forward/Reflected RF power 2. Over pulse width/duty cycle 3. DC power supply fault 4. Thermal fault		
Front panel controls	1. AC power	2. Pulse width	3. Duty cycle
Cooling	Internal forced air		
Operating temperature	+10 to 40°C		
AC line voltage	208/230 VAC, $\pm 10\%$ , 47 - 63 Hz		
AC power requirements	700 VA		
Package	Rack mount		
Size (HWD, inches)	8.75 x 19.0 x 22.0		
Net weight	75 lbs.		



Herley reserves the right to change specifications and/or discontinue this product without notice. © Herley Industries, Inc., 2001

**Herley Medical Products**, Division of Herley Industries, 3061 Industry Drive, Lancaster, PA 17603  
Phone (717) 397-2777 Fax (717) 397-7079 Website: [www.herley.com](http://www.herley.com)