



Model 3900A-11

ISO 9001 CERTIFIED

**6 - 220 MHz, pulsed,
solid-state, RF power
amplifier system**

Electrical specifications:

Frequency range
Pulse power (min.) into 50 ohms
CW power (max.) into 50 ohms
Gain (typ.)60 dB
Gain flatness
Input/Output impedance
Input VSWR
Pulse width (Max/ch)
Duty cycle
Amplitude rise/fall time
Amplitude droop

Noise figure
Output noise (blanked)
Blanking delay

(-1) Ch B:	(-1) Ch A:
6 - 220 MHz	6 - 220 MHz
300 W	300 W (not simultaneous)
30 W	30 W (not simultaneous)
60 dB	
±3 dB	±3 dB
50 ohms	
< 2:1	
20 ms, 1 ms simultaneous	
10%, 1% simultaneous	
200 ns typ.	200 ns typ.
CH B: <5% to 10 ms typ.; 7% max.	
CH A: <5% to 10 ms typ.; 7% max	
8 dB typ.	8 dB typ.
< 20 dB over thermal	
< 2 µs on/off, TTL signal	

Protection

1. VSWR: infinite VSWR at rated power
2. Input overdrive: up to 10 dB
3. Over duty cycle/pulse width
4. Over temperature

Supplemental characteristics:

Connectors, rear panel (2ea)

1. RF input: BNC (F)
2. RF outputs: Type N (F)
3. Noise blanking: BNC (F)
4. Interface: 25 pin D(F), EMI filtered

Controls, front panel

1. AC power
2. Duty cycle
3. Duty cycle

Indicators, front panel

1. AC power on
2. Over pulse width
3. Over duty cycle
4. Over temperature
5. Overdrive
6. CW mode
7. FWD/RFL power

System monitors

1. Thermal fault
2. DC power supply fault
3. Over duty cycle/pulse width
4. Forward/reflected RF power

Cooling
Operating temperature
AC line voltage
AC power requirements
Package
Size (HWD, inches)
Net weight

Internal forced air
+10 to 40°C
120/240 VAC, ±10%, 50 - 60 Hz
1300 watts
Rack mount
5.25x19x24
75 lbs